



Stamtec

Model-S2-300
MFG No-S90969
MFG Date- 1999.12
Capacity- 300 Ton
Rating Point- 0.354
Stroke No. 30-60
Stroke 9.84 IN
Die Height 27.56
Slide Adjustment-7.87
Slide Area- 98.43 X 55.12
Bolster Area 98.43 X 55.12



Note- They currently have an 8" spacer in, that can be removed.



Coil Handling for StamTec
 Model-BGY-H-10-15
 Max Coil Weight 10,000 Lbs
 STK Width 50 IN
 Max Coil O.D. 60 IN

COIL HANDLING EQUIPMENT GENERAL DATA PLATE			
MODEL NO.	BGY-H-10-15	SERIAL NO.	R030507-9
MAX. COIL WT.	10,000 LBS.	MAX. COIL O.D.	60 IN
MANDREL EXPANSION RANGE			IN
STK. WIDTH	50 IN.	FEED LGTH	IN
STK. IN. MAX. STEEL			IN.
MACHINE DIRECTION	R-L	MTG. POSITION	
SPEED	IPM		SPM
PASS LINE	IN.	AIR SUPPLY	60 TO 80 PSI.
POWER SUPPLY	460 V.	3 PH	60 HZ
SEE MANUAL OR CONSULT FACTORY			



Coil Handling

Model- 10050-H-DSJ

S/N-R030507-5

Max Coil wt- 10,000 LBS

STK Width 50 IN

Machine Direction R-L

Mandrel Expansion Range 15.75-20.25

**COIL HANDLING EQUIPMENT
GENERAL DATA PLATE**

MODEL NO. 10050-H-DSJ SERIAL NO. R030507-5

MAX. COIL WT. 10,000 LBS. MAX. COIL O.D. 60 IN

MANDREL EXPANSION RANGE 15.75 To 20.25 IN

STK. WIDTH 50 IN FEED LGTH IN

STK. THK. IN MILD STEEL IN

MACHINE DIRECTION R-L MTG. POSITION

SPEED IPM SPM

PASS LINE IN AIR SUPPLY 60 TO 80 PSI

POWER SUPPLY 460 V. 3 PH. 60 HZ

SEE MANUAL OR CONSULT FACTORY

Press Leveler

Model- C9-50

S/N R090507-3

STK Width 50 IN

STK THK In Mild Steel- .085/ Full width IN

Speed 160 IPM

**COIL HANDLING EQUIPMENT
GENERAL DATA PLATE**

MODEL NO. C9-50 SERIAL NO. R090507-3

MAX. COIL WT. LBS. MAX. COIL O.D. IN

MANDREL EXPANSION RANGE IN

STK. WIDTH 50 IN FEED LGTH IN

STK. THK. IN MILD STEEL .085/ FULL WIDTH IN

MACHINE DIRECTION R-L MTG. POSITION

SPEED IPM SPM

PASS LINE IN AIR SUPPLY PSI

POWER SUPPLY V. PH. HZ

Feeder

Model- PM DOM . 083 . 250

S/N-R030507.1

STK Width 50 IN

STK THK in Mild Steel .074

Speed 300 IPM

Pass Line 49 IN

**COIL HANDLING EQUIPMENT
GENERAL DATA PLATE**

MODEL NO. PM DOM .083 . 250 SERIAL NO. R030507.1

MAX. COIL WT. LBS. MAX. COIL O.D. IN

MANDREL EXPANSION RANGE IN

STK. WIDTH 50 IN FEED LGTH IN

STK. THK. IN MILD STEEL .074 IN

MACHINE DIRECTION R-L MTG. POSITION

SPEED 300 IPM SPM

PASS LINE 49 IN AIR SUPPLY PSI

POWER SUPPLY 480 V. 3 PH. 60 HZ

SEE MANUAL OR CONSULT FACTORY